

## 1330 nm laser diode - DFB

Model 4 : >120 mW / singlemode fiber / 14 pin Butterfly with isolator / SMF or PMF

Reference: 1330LD-4-0-0 (-1 : SMF ; -2 : PMF)

Technology : DFB\*

SPECIFICATIONS	Unit	Min	Typ	Maximum
Output Power (CW mode)	mW	120		
Output Power (Pulse mode)	mW		>180	
Center Wavelength (CW)**	nm	1325	1330**	1335
Isolator (Note : contact us for special version with no isolator or double stage isolator)	dB		25	
Spectral Width (FWHM)	KHz		200	500
Threshold Current	mA		15	30
Operating Current	mA		400	600
Operation Voltage	V		2.0	2.5
Wavelength shift w Temperature	nm/°C		0.08	
Wavelength shift w Current	nm/mA		0.003	
Side mode suppression ratio	dB	35	50	
Internal Photodiode Responsivity	mA/W	5		
Internal Photodiode Dark Current	nA			500
TEC current (-5/60°C)	A			1.5
TEC Voltage (-5/60°C)	V			2.0
Internal thermistor (25°C)	kΩ	9.5	10	10.5
Fiber type	SMF28-e/ultra or equivalent (PM version : PM1300 or eq.)			
Coating diameter	μm		900	
Fiber bend radius	mm			30
Storage case temperature	°C	-40 (abs min)		70 (abs max)
Case operating temperature	°C	-20		60
Lead soldering temperature	°C		260	300
Laser diode reverse voltage	V			15
Butterfly pin configuration***	Type-1***			
Pigtail termination	FC/APC connector			
Polarization state (PM version)	Aligned to the slow axis			

\*: See our tutorial : [fiber coupled laser diode](#)

\*\* : Possibility to specify a precise wavelength – contact us

\*\*\* : Possibility to request another butterfly pin configuration: Type-2, Type-2 bias-T, Type 2 bias-T anode grounded...

Form factor & laser diode pin configuration (standard 14-pin Butterfly Type-1)\*\*\* :

