

1550 nm laser diode

28 W / Fiber : 105 μ m-core / NA=0.22

Reference: 1550LD-8-0-0

SPECIFICATIONS	Unit	Min	Typ	Maximum
Output Power	W	25	28	30
Center Wavelength	nm	1530	1550	1570
Spectral Width (FWHM)	nm		20.0	
Threshold Current	A		0.3	
Operating Current	A		10	12.0
Operation Voltage	V		25	30
Conversion Efficiency	%		12	
Wavelength shift w Temperature	nm/°C		0.5	
Wavelength shift with current	nm/A		1-2	
Slope Efficiency	W/A		4.0	
Storage Temperature	°C	-30		70
Case Operating Temperature	°C	15	25	45
Minimum Fiber Bend Radius	mm	30		
Fiber Buffer/tube Diameter	μm		900	
Fiber Clad Diameter	μm		125	
Fiber Core Diameter	μm		105	
Numerical Aperture	NA		0.22	
Soldering Temperature	°C			260
Soldering time	s			10
Dimensions	mm	80*80*25		
Mounting holes diameter/distance	mm	Ø3.2 / 74.4 * 38		
Fiber connector	Yes (SMA905)			
ROHS Compliant	Yes			
Please solder the pins when the level of current is over 6A				

Please solder the pins when the level of current is over 6A

